

# Wall2Floor Component B

Additive in powder for Wall2Floor Top Coat.

## DESCRIPTION

**Wall2Floor Component B** is a special additive in powder for the "Wall2Floor System".

## USES

To use as an additive for the **Wall2Floor Top Coat** only.

## FEATURES

Product in powder

## SUBSTRATE PREPARATION

Please refer to the "Wall2Floor System" technical data sheet.

## APPLICATION

Please refer to the "Wall2Floor System" technical data sheet.

## DILUTION

Add **Wall2Floor Component B** to **Wall2Floor Top Coat**, before the application following the recommendation listed in the "Wall2Floor System" technical data sheet. The mixing phase must be gently and operated always using a mechanical drill/agitator for 3 minutes approx.

Product pot life after the mixing phase: 90 minutes.

## TOOLS CLEANING

With water, immediately after use

## COLOURS

White

## PACKAGING

5 Kg BAG.

## SHELF LIFE

The packaged product has guaranteed for 12 months, if stored in the original sealed package and at temperatures between +5°C and +35°C.

Irritant / risk of serious eye damage / irritation of the skin / Keep out of the reach of children / avoid contact with eyes / in case of contact with eyes, clean the up immediately with fresh water and seek medical advice / wear suitable gloves and protect eyes / face / not breathe dust / If swallowed, seek medical advice immediately and show this container or label. The product must be transported, stored and used in accordance with current standards of hygiene and safety, let dry completely and treat them as special waste. For more information see the safety data sheet

NB- NOVACOLOR ensures that the information herein has been provided to the best of its experience and its technical and scientific knowledge, but cannot take any responsibility for the results obtained by using them as the conditions of application are beyond its control. We recommend to check the suitability of the product to each specific instance. This TDS cancels and replaces all previous editions.